


Inventors: Stephen C. Oberheim

*I hereby certify that this paper is being deposited with the United States Postal Service as EXPRESS MAIL in an envelope addressed to: MS Patent Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on this date.*

10/14/2003  
Date

  
Express Mail No. EV032698107US

AN IMPROVED DEPTH ROD ADJUSTMENT  
MECHANISM FOR A PLUNGE-TYPE ROUTER

1 AN IMPROVED DEPTH ROD ADJUSTMENT  
2 MECHANISM FOR A PLUNGE-TYPE ROUTER

3 The present invention generally relates to power hand tools and, more  
4 particularly, to plunge-type routers.

5 BACKGROUND OF THE INVENTION

6 Plunge-type routers are well known and commonly used to cut grooves,  
7 edges and a variety of shapes in work pieces made of wood and other materials. The  
8 shapes are determined by the kind and shape of router bits used, the depth of cut of the bit  
9 and the path of travel by the router bit relative to the work piece. A plunge router is  
10 constructed to move the router bit toward and away from the work piece when the router  
11 is being operated in a freehand manner. It can often also be mounted to a router table so  
12 that the router bit extends through an opening in the top of the table. The depth of cut of  
13 the router bit is typically determined by an adjustable depth stop system which may or  
14 may not include means for locking the router in its plunged position.

15 During freehand operation, the plunge router may be supported on the work  
16 piece with the bit retracted and placed in the desired location so that when it is turned on  
17 and plunged downwardly, the router bit advances into the work piece and the operator  
18 then moves it relative to the work piece to complete the desired routing operation. To do  
19 the plunging operation, the operator must exert a downward force on the motor housing  
20 assembly, generally by pressing on attached handles to move the router bit into contact  
21 with the work piece. The motor housing assembly is typically biased to automatically  
22 retract the router bit from the work piece when the downward force imparted by the  
23 operator is removed.

24 Plunge routers generally include a plunge adjustment mechanism that  
25 enables the operator to control the distance the router bit can move toward the work piece

1 and thereby determine its depth of cut. As is well known to those who have used plunge  
2 type routers, the adjustment of the stop system must be carefully done to achieve the  
3 desired depth of cut. Because the type and size of various router bits are very different, it  
4 is prudent if not necessary to recalibrate or reset the adjustment means after any  
5 manipulation of the router bit to insure that it has been accurately set to achieve the  
6 desired depth of cut. There are many other devices that attempt to accurately set the  
7 depth adjustable stop to provide an accurate depth of cut, including adjustable rods,  
8 scales with indicators, micrometer type adjusters and other systems. Such adjustable stop  
9 mechanisms in the prior art are generally hand manipulated and some may have a printed  
10 scale or other indicia located on the mechanism for use in providing a specified depth of  
11 cut. However, it is still necessary for users to carefully measure the depth of cut in one  
12 way or another to insure that the desired cut will be made. In this regard, it is often  
13 common practice to perform a test cut on a scrap piece and actually measure the result  
14 and to iteratively adjust the stop mechanism until the proper result is achieved.

## 15 SUMMARY OF THE INVENTION

16 A plunge-type router is disclosed which is useful for either freehand or  
17 router table mounted operation. The router has a base and a motor housing assembly  
18 with the base being adjustable relative to the motor housing assembly and operates in a  
19 conventional plunge router operation, but has an depth rod adjusting and measuring  
20 mechanism that includes an electronic measuring system with a digital display and  
21 control functionality that enables a user to accurately measure the position of a depth rod  
22 and thereby accurately set a depth of cut value which is displayed on a digital readout.

23 Alternate embodiments include motorized depth adjusting mechanisms to  
24 adjust the depth rod position and thereby adjust the depth of cut of the router during  
25 operation, as well as an embodiment that is a hybrid router which has a removable motor  
26 assembly that can be coupled to a plunge-type router base.

## DESCRIPTION OF THE DRAWINGS

FIGURE 1 is a perspective front view a preferred embodiment of the plunge router of the present invention;

FIG. 2 is another perspective front view of the router shown in FIG. 1 with portions removed ;

FIG. 3 is an idealized view of the side of a portion of the construction of the embodiment shown in FIGS 2 and 3;

FIG. 4 is a perspective front view of a second preferred embodiment of the plunge router of the present invention, with portions removed and illustrating in idealized fashion the internal construction of the embodiment; and

FIG. 5 is a perspective front view of a third preferred embodiment of the plunge router of the present invention, with portions removed and illustrating in idealized fashion the internal construction of the embodiment;

FIG. 6 is a perspective front view of a fourth preferred embodiment of the plunge router of the present invention, with portions removed and illustrating in idealized fashion the internal construction of the embodiment, this embodiment comprising a manually operable embodiment that is similar to the motorized embodiment of FIG. 5;

FIG. 7 is a perspective front view of a fifth preferred embodiment of the plunge router of the present invention, this embodiment comprising a manually operable embodiment that is similar to the embodiment of FIGS 1-3, but configured as a hybrid router, with the motor assembly being mounted in a plunge router base;

FIG. 8 is a front view of the display that is incorporated into several of the illustrated embodiments.

## DETAILED DESCRIPTION

A preferred embodiment of the present invention is shown in FIGS. 1-3 and is indicated generally at 10. The router has a motor housing assembly 12 that includes a pair of handles 14 that are preferably integrally formed with the housing assembly. The router has a digital display 16 that includes a pair of pushbutton switches 18 and 20 that are used to control the manner in which the display operates and to determine the setting of the depth of cut as will hereinafter be explained. The housing assembly 12 is connected to a base 22 by a depth adjusting assembly, indicated generally at 24, which includes a pair of plunge posts 26 and 28 that fit in and are moveable relative to cylindrical channels 30 and 32 that are part of the housing assembly 12. The router 10 is a plunge type router in that when a lock 34 is released by the user, the housing assembly can be raised and lowered relative to the base 22 to control the depth of cut of a router bit 36 that is secured in a collet 38 that is attached to the output shaft of a motor (not shown) that is a part of the housing assembly 12.

The housing assembly is generally biased in the upward direction so that it will automatically raise itself relative to the base 22 when the locking mechanism 34 is released. During operation, when a user releases the locking mechanism 34 and forces the handles downwardly, the router bit 36 will engage a work surface. The depth of the cut that may be made is a function of the amount of downward movement by the housing assembly. To accurately cut at a desired depth, a depth rod 40 which is part of a depth rod adjustment mechanism indicated generally at 42 can be vertically adjusted relative to the base 22. A rotatable turret 44 may be provided to assist in providing different predetermined depth of cut set positions.

The depth rod adjusting mechanism 42 includes a locking lever 46 which has a threaded screw that engages a threaded opening in a boss 48. The end of the screw

1 is capable of contacting the side of the depth rod 40 to secure its position when the  
2 locking lever 46 is rotated into engagement with it.

3 Referring to FIG. 2, an adjusting knob 50 is connected to a pinion gear 52  
4 (see FIG. 3) that has outer teeth that engage a rack that is formed in one face of the depth  
5 rod 40. A sensor rail 54 is attached to the depth rod by screws 56 or the like so that when  
6 the knob 50 is rotated, the pinion gear will cause the depth rod to be vertically moved in  
7 an incremental manner, assuming that the locking lever 46 has been loosened. A sensor  
8 element 58 is secured to the housing assembly 12 by screws 60 and the sensor rail 54 has  
9 copper pads along its length that are positioned to provide a changing capacitance that is  
10 sensed by the sensor element 58 and which can thereby provide accurate measurement of  
11 incremental positions along the length of the rail. In this regard, it is preferred that the  
12 sensor rail and sensor element be similar to those that are presently used in commercially  
13 available digital calipers. Other linear sensor technologies based on inductance,  
14 magnetostrictive effects or resistive elements can also be used. The signals that are  
15 sensed by the sensor element are applied to a ribbon connector 62 that extends to a  
16 printed circuit board that contains the digital display 16, which is also shown in detail in  
17 FIG. 8. The sensor is very accurate and may measure depth changes to hundredths of an  
18 inch or in tenths of a millimeter.

19 To set a depth of cut, the locking lever 46 is first loosened so that the depth  
20 rod 40 can be adjusted. The operator then presses down on the handle so that the router  
21 bit 36 is brought into contact with the work surface and the lock 34 is then applied to hold  
22 the bit in contact with the work surface. The user then adjusts the knob 50 to bring the  
23 depth rod 40 into contact with one of the five surfaces of the turret 44. The user then uses  
24 the locking lever 46 to lock the depth rod 40 in place. The operator then depresses the  
25 pushbutton 20 to reset or zero the display. After that has been done, the user unlocks the  
26 locking lever 46 so that the depth rod can be moved, and he then adjusts the knob 50 to  
27 raise the depth rod 40 while watching the digital display 16 until the desired plunge depth

1 is indicated on the display, whereupon the user then tightens the locking lever 46 to lock  
2 the depth rod 40 in place. The plunge depth has then been accurately set.

3 This embodiment is adapted to be mounted to a router table which inverts  
4 the router so that the router bit will extend through an opening and engage the underside  
5 of a work piece. When used in such a router table, the rod is locked to the turret 44 and  
6 the adjusting knob 50 acts to raise and lower the motor housing and thereby adjust the  
7 protrusion height of the bit above the table surface. The depth rod can be adjusted, the  
8 display zeroed and the depth of cut determined by manipulating the knob 50 while  
9 viewing the display.

10 A second and third embodiment of the router is shown in FIGS. 4 and 5.  
11 Reference numbers in these embodiments may be the same as that used in the  
12 embodiment shown in FIGS 1-3 for components that are common to the embodiments  
13 and are similar to one another. It is not intended that components that have the same  
14 number in various embodiments necessarily be of identical construction. The common  
15 numbers are used for the sake of convenience.

16 With regard to the second embodiment shown in FIG. 4, this embodiment  
17 includes a motor 64 which is positioned to drive a gear mechanism 66 that has an output  
18 connected to a pinion gear 68 that engages the teeth of the rack portion of the depth rod  
19 70 that extends to a generally cylindrical lower end portion 72 that has an annular recess  
20 74 which defines an enlarged end 76. The end 76 is adapted to penetrate an enlarged  
21 opening 78 in the rotatable turret 40 and engage and be retained by a smaller keyhole  
22 portion 82 when the turret 44 is rotated. This embodiment also includes a pair of  
23 pushbuttons 84 and 86 which will activate the motor 64 to move it in the direction of the  
24 arrows. During operation of this embodiment, the user can use the motor 64 to bring the  
25 router bit into contact with the work piece similarly as described with regard to the first  
26 embodiment, zero the display and then the pushbuttons 84 and 86 to adjust the position of  
27 the depth rod 70 while reading the digital display. When the proper depth of cut is

1 reached, the user releases the pushbutton that was running the motor 64 and the depth of  
2 cut has been set.

3 In this second embodiment, the router is adapted to be mounted to a router  
4 table which inverts the router so that the router bit will extend through an opening and  
5 engage the underside of a work piece as it is being manipulated on the router table. By  
6 locking the depth rod 70 into the keyhole 82, activation of the motor 64 will physically  
7 move the housing assembly 12 relative to the base 22. If the router is mounted in a router  
8 table, the display 16 can be inverted so that a user can read the depth of cut without  
9 reading it upside down.

10 A third embodiment of the router employs a motor 90 that drives a gear  
11 mechanism 92 that in turn drives a threaded output shaft 94 that engages the interior  
12 threads of a depth rod 96 that has an end portion 98 for engaging the turret 44. The motor  
13 90, and gear mechanism 92 are mounted in the housing in a fixed position. While not  
14 shown, an outwardly extending anti-rotation pin is or the like is attached to the depth rod  
15 96 and is configured to ride in a vertical recess or slot to prevent the depth rod from  
16 rotating when the shaft 94 is rotated. This assures that rotation of the output shaft 94 will  
17 cause the depth rod to move vertically relative to the housing 12. Pushbuttons 84 and 86  
18 also control the operation of the motor to either raise or lower the depth rod 94 as in the  
19 second embodiment of the router. The end portion 98 of the depth rod has the same  
20 configuration as in the second embodiment so that the locking lever 80 can hold the depth  
21 rod in the same manner as in the second embodiment. This similarly enables the router to  
22 be mounted to a router table and have the depth of cut be accurately determined in the  
23 same manner as described with respect to the second embodiment. It should be  
24 appreciated that the embodiment of FIG 1 can also incorporate the turret 44 having a  
25 keyhole 82 configuration but adjustment of the depth of cut must be done manually.  
26 However, the depth of cut can be accurately measured and displayed.



1           A fourth embodiment is shown in FIG. 6 which is similar to the  
2 embodiment of FIG. 5, except that it is a manually operable embodiment. A top  
3 extension 100 of a shaft 94' engages a knob 102 that can be manually rotated by a user.  
4 When the knob is rotated, the shaft 94' rotates and causes the depth rod 96 to move  
5 vertically. A locking lever similar to the locking lever 46 used in the embodiment shown  
6 in FIGS. 1-3 may be provided if desired.

7           A fifth embodiment is shown in FIG. 7 and comprises a hybrid router,  
8 indicated generally at 110, that has a plunge base assembly, indicated generally at 112, in  
9 which a motor assembly 114 can be attached. As shown, the motor assembly 114 is  
10 generally cylindrically shaped and can be inserted into a mounting portion 116 that has a  
11 cylindrical opening. The motor assembly has an output shaft to which a collet assembly  
12 118 is preferably attached for securing a router bit or other tool to the router during  
13 operation attachment. The plunge base assembly 112 has a vertically oriented housing  
14 120 in which a depth rod adjusting mechanism is contained, with the mechanism being  
15 similar to the embodiment of FIGS 1-3 in that it has a rack and pinion operation, with the  
16 rack having a lower portion defining a depth rod 122, similar to the configuration shown  
17 in FIG. 3. It should also be understood that the embodiments shown in FIGS 4-6 may be  
18 utilized in the hybrid router. If motorized embodiments are utilized, power must be  
19 provided from the motor assembly by a suitable cable and connector arrangement. A  
20 pinion gear is attached to a knob 124 and a locking knob 126 is also provided to lock the  
21 depth rod 122 in place once it has been positioned at a desired elevation. In a similar  
22 manner as has been described with regard to the embodiment of FIGS. 1-3, a sensor rail  
23 is attached to the depth rod and a sensor element is secured to the plunge base assembly  
24 for generating digital signals that are indicative of the position of the sensor element  
25 along the rail as previously described, which are displayed in a display 126 that is similar  
26 to the display 16 shown in FIG. 8

1           With regard to the display 16 and referring to FIG. 8, it is shown to have  
2 the display button 18 and a zero/scale button 20. In this regard, the actual buttons 18 and  
3 20 may be mounted in the housing assembly 12 itself or may be located on a printed  
4 circuit board 130 and extend through an opening in the housing assembly. The preferred  
5 display 16 utilizes the pushbuttons 18 and 20 to change the functionality of the display.  
6 As shown, there are six 7-segment characters 132 as well as two slashes 134 and two  
7 decimal points 136 in addition to an inch icon and a millimeter icon. In the event that the  
8 speed of the motor powering the router bit can be adjusted, a constant RPM icon may be  
9 present or the operating speed of the motor may be displayed with the characters 102.

10           The display 16 is preferably designed to turn on with the same units that  
11 existed before the router was turned off and also operates as follows. If the display  
12 button 18 is pressed for less than 1/2 second, it may temporarily change the display and  
13 then return to the default after two seconds. If the display button is pressed for longer  
14 than 1/2 second, the display may cycle between speed adjustment and display, depth of  
15 cut as well as inverted (i.e., upside down) speed and inverted depth of cut. The zero/scale  
16 button when pressed for less than 1/2 second resets the depth of cut to zero and if it is  
17 held for more than 1/2 second, the scale will change from metric to inches or vice versa.  
18 When the change is made, the appropriate mm or inch icon will be switched on and off.  
19 The display buttons can also be designed operate in a non time dependent way. In this  
20 type of display, the display button cycles the display between displaying speed, depth of  
21 cut in English or metric numbers and depth of cut using inverted English or Metric  
22 numbers. The zero/scale button would act to zero the measurement.

23           When in the speed adjustment and display mode, the switches 84 and 86  
24 can be used to adjust the operating speed of the main router drive motor. While the  
25 display 16 shown in the embodiment of FIGS 1-3 does not show the up and down  
26 switches, they may be provided if desired. Because the embodiment of FIG. 7 has a  
27 removable motor assembly, the display 126 preferably does not interact with the motor

1 assembly to control and display the motor speed. However, such capability is possible  
2 with appropriately configured electrical connectors that would be provided to  
3 interconnect the display with motor control circuitry. Also, it should be understood that  
4 the displays 16 and 126 are preferably powered by accessible, replaceable batteries that  
5 are not shown, but which are known to those skilled in the art. The display can also be  
6 powered off the line voltage, using batteries to preserve stored values in memory when  
7 the line cord is not connected.

8           With regard to the measurements that are displayed, the appropriate  
9 decimal point will be illuminated depending upon whether the display is displaying  
10 upright or inverted when English or metric is used. If fractions are used, then the  
11 appropriate slash will also be illuminated. The measurement is right justified according  
12 to whether the decimal point or slash is used.

13           While various embodiments of the present invention have been shown and  
14 described, it should be understood that other modifications, substitutions and alternatives  
15 are apparent to one of ordinary skill in the art. Such modifications, substitutions and  
16 alternatives can be made without departing from the spirit and scope of the invention,  
17 which should be determined from the appended claims.

18           Various features of the invention are set forth in the following claims.